

トラクター	馬力	ホイールベース	前方注視点距離	作業時最大舵角	操舵量 (高速時)	操舵量 (低速時)	追従性 (スタート時)	追従性 (収束時)	応答性	応答予測時間	遊び度合い	オーバーライド感度	自動操舵開始時の ステアリング位置を センターとする	ステアリングセンター 自動調整	走行安定時に 作業時最大舵角を 自動調整する
クボタ_KL500	50	2.00	3.00	20.0	20	20		20	10	1.00	1.00	20	OFF	ON	ON
クボタ_KL53	53	1.92	3.00	20.0	20	20	30	30	10	1.00	4.00	20	OFF	ON	ON
クボタ_GRANDMAX(GM64)	64	2.15	3.00	20.0	20	30	30	30	10	1.00	4.00	20	OFF	ON	ON
クボタ_GM73	73	2.15	3.00	20.0	16	20	20	20	5	1.00	1.00	20	OFF	ON	ON
クボタ_GM73	73	2.15	3.00	20.0	9	20	9	9	5	1.00	4.00	20	OFF	ON	ON
クボタ_GM73	73	3.00	3.00	20.0	20	20	20	20	10	1.00	1.00	20	OFF	ON	ON
クボタ_GVK760	76	2.50	3.00	40.0	11	11	17	17	20	0.25	4.00	30	OFF	ON	ON
クボタ_DREAM21(MD7530DT)	79	2.15	3.00	20.0	5	10		30	6	2.50	3.00	25	ON	ON	ON
クボタ_MD87	87	2.30	2.30	20.0	15	30		30	7	2.00	2.00	23	ON	ON	ON
クボタ_M90	90	2.30	3.00	20.0	15	25		35	7	2.20	4.00	23	ON	ON	ON
クボタ_M105D	105	2.45	3.00	20.0	15	25		40	8	1.00	2.00	23			
クボタ_M110G	110	2.60	5.00	20.0	80	90		51	5	2.00	0.10	20	ON	ON	ON
クボタ_M110G-AT	110	2.40	3.00	20.0	15	30	100	30	6	1.00	1.00	20	OFF	ON	ON
クボタ_Grandom(M115D)	115	2.70	3.00	20.0	10	10	25	25	7	1.00	3.00	23	OFF	ON	ON
クボタ_M125GE	125	2.70	3.00	20.0	15	20	50	50	10	1.00	4.00	20	OFF	ON	ON
クボタ_M125GE	125	2.70	3.00	20.0	30	30	30	30	10	1.00	4.00	20	OFF	ON	ON
クボタ_M135GE	135	2.75	3.00	20.0	40	60		40	7	1.00	1.00	20			
クボタ_M7151	150	2.70	3.50	20.0	20	20		20	8	1.50	1.50	25	ON	ON	ON
イセキ_PZP80	田植機	1.25	3.25	20.0	8	8		53	13	1.50	2.50	20	OFF	ON	ON
イセキ_PZP80	田植機	1.25	3.25	20.0	6	5	28	28	25	1.60	2.50	20	OFF	ON	ON
イセキ_TJV783	78	3.00	4.00	15.0	8	11	10	10	5	3.00	1.50	14	ON	ON	ON
イセキ_TJV783	78	3.00	3.00	22.0	24	26	24	20	7	2.00	8.00	20	ON	OFF	OFF
イセキ_TJW105	105	3.00	3.00	20.0	8	20		30	7	1.00	1.00	16	OFF	ON	
イセキ_TJW105	105	2.40	3.00	20.0	15	25		40	7	2.50	3.00	23	ON	ON	
イセキ_BIG-T7160	160	3.00	3.00	20.0	40	60		40	6	1.00	1.00	20	OFF	ON	ON
MF_6160	100	2.70	3.00	20.0	60	60		40	7	1.00	1.00	20	OFF	ON	ON
MF_6280	110	2.70	3.00	20.0	70	85		45	7	1.00	5.00	20	OFF	ON	
MF_6280	110	2.70	3.00	20.0	60	60		40	7	1.00	4.00	20	OFF	ON	
MF_6280	110	2.70	3.00	20.0	85	85		41	7	1.00	5.00	20	OFF	ON	
NH_T5050	95	2.37	3.00	20.0	20	30	20	20	5	1.00	5.00	25	ON	ON	ON
NH_TM140	140	2.80	3.00	20.0	35	40		40	7	1.00	1.00	20	OFF	ON	ON
ヤンマー_EG65	65	2.12	2.12	43.0	50	75		20	8	1.00	5.00	28			